©OUTLANDER™ MAX LIMITED 1000R

HIGHLIGHTS

- Rotax® V-twin engine
- Rear Air Control Suspension (ACS) with FOX† Air Assist shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- Garmin† Montana† 650t touchscreen GPS
- 1,361 kg WARN[†] winch with roller fairlead
- Heavy-duty front and rear bumpers
- 14-in. cast-aluminum wheels with LIMITED finish
- 26-in. ITP[†] Terracross radial tires

- · Painted plastics for premium look
- Handlebar wind deflectors
- Multifunction Analog / Digital gauge
- Mudguards
- · Comfort grips



ENGINE	1000R
Туре	89 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm 22.9 cm travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 23.6 cm travel
Rear Shocks	Air Control Suspension (ACS) with FOX Air Assist

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHE	ELS
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum with LIMITED finish

DIMENSIONS / CAPACITIES		
LxWxH	238.8 x 116.8 x 135 cm	
Wheelbase	149.9 cm	
Ground Clearance	27.9 cm	
Seat Height	87.7 cm	
Dry Weight*	381 kg	
Rack Capacity	Front: 45 kg Rear: 90 kg	
Storage Capacity	Rear: 21.4 L	
Towing Capacity	590 kg	
Fuel Capacity	20.5 L	

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter,	Instrumentation	Integrated / removable Garmin Montana 650t touchscreen GPS, Lighter type DC outlet in console, standard connector in the back (15-A)
	4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
Winch	1,361 kg WARN winch with roller fairlead	Seat	Convertible Rack System (CRS)
Protection	Heavy-duty front & rear bumpers, handlebar wind deflectors, mudguards	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)

WARRANTY	
Factory	2 years
Extended	Up to 36 months B.E.S.T. coverage



