©OUTLANDER™ MAX XT 650™

- Rotax® V-twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg WARN† winch with roller fairlead
- Heavy-duty front and rear bumpers
- 14-in. cast-aluminum wheels
- 26-in. ITP[†] Terracross radial tires
- · Painted plastics for premium look
- · Handlebar wind deflectors
- Convertible Rack System (CRS) with LinQ™ system
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips

- · Raised floorboards
- 21.4 L water-resistant rear compartment
- 625-W magneto



Brushed Aluminum & Can-Am Red

| ENGINES | 650 |
|----------------------|---|
| Туре | 62 hp, Rotax 649.6 cc V-twin, liquid cooled |
| Fuel Delivery System | Electronic Fuel Injection (EFI) |
| Transmission | CVT, P / R / N / H / L, standard engine braking |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |

| ruei Delivery System | Electronic Fuel injection (EFI) | | |
|----------------------|---|--|--|
| Transmission | CVT, P / R / N / H / L, standard engine braking | | |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential | | |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) | | |
| | | | |
| SUSPENSIONS | | | |
| Front Suspension | Double A-arm 22.9 cm travel | | |

| SUSPENSIONS | |
|------------------|--|
| Front Suspension | Double A-arm 22.9 cm travel |
| Front Shocks | Oil |
| Rear Suspension | Torsional Trailing arm Independent (TTI) 23.6 cm travel |
| Rear Shocks | Oil |
| | |

| BRAKES | |
|--------|--|
| Front | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear | Single 214 mm ventilated disc brake with hydraulic twin-piston caliper |

| TIRES / WHEELS | |
|----------------|--|
| Front Tires | ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm) |
| Rear Tires | ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm) |
| Wheels | 14-in. cast-aluminum |

| DIMENSIONS / CAPACITIES | |
|-------------------------|-----------------------------|
| LxWxH | 238.8 x 116.8 x 135 cm |
| Wheelbase | 149.9 cm |
| Ground Clearance | 27.9 cm |
| Seat Height | 87.7 cm |
| Dry Weight* | 361 kg |
| Rack Capacity | Front: 45 kg Rear: 90 kg |
| Storage Capacity | Rear: 21.4 L |
| Towing Capacity | 590 kg |
| Fuel Capacity | 20.5 L |

| FEATURES | | | |
|-----------------|--|-------------------|--|
| Gauge | Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock | Instrumentation | Lighter type DC outlet in console, standard connector in the back (15-A) |
| | | Lighting | 230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light |
| | | Seat | Convertible Rack System (CRS) |
| Winch | 1,361 kg WARN winch with roller fairlead | Anti-theft System | RF Digitally Encoded Security System (D.E.S.S.™) |
| Protection | Heavy-duty front & rear bumpers, handlebar wind deflectors | | |

| WARRANTY | |
|----------|-----------------------------------|
| Factory | 2 years |
| Extended | Up to 36 months B.E.S.T. coverage |



