## **©OUTLANDER™ MAX XT-P 850™**

## PACKAGE HIGHLIGHTS

- Rotax® V-twin engine
- Front and rear FOX<sup>†</sup> 1.5 PODIUM<sup>†</sup> QS3 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg WARN† winch with roller fairlead
- 14-in. cast-aluminum beadlock wheels
- 26-in. ITP<sup>†</sup> Terracross radial tires
- Painted plastics for premium look
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad

- Multifunction Analog / Digital gauge
- Convertible Rack System (CRS) with LinQ<sup>™</sup> system
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips



Triple Black

| ENGINES              | 850   |
|----------------------|---|
| Туре                 | 78 hp, Rotax 854 cc V-twin, liquid cooled                               |
| Fuel Delivery System | Electronic Fuel Injection (EFI)   |
| Transmission         | CVT, P / R / N / H / L, standard engine braking                         |
| Drive Train          | Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential |
| Power Steering       | Tri-Mode Dynamic Power Steering (DPS)                                   |

| HODENGIONO       |  |
|------------------|--|
| SUSPENSIONS      |  |
| Front Suspension | Double A-arm<br>22.9 cm travel                             |
| Front Shocks     | FOX 1.5 PODIUM QS3   |
| Rear Suspension  | Torsional Trailing arm Independent (TTI)<br>23.6 cm travel |
| Rear Shocks      | FOX 1.5 PODIUM QS3   |

| BRAKES |  |
|--------|--|
| Front  | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear   | Single 214 mm ventilated disc brake with hydraulic twin-piston caliper |

| TIRES / WHEE | LS   |
|--------------|--|
| Front Tires  | ITP Terracross 26 x 8 x 14 in.<br>(66 x 20.3 x 35.6 cm)  |
| Rear Tires   | ITP Terracross 26 x 10 x 14 in.<br>(66 x 25.4 x 35.6 cm) |
| Wheels       | 14-in. cast-aluminum beadlock                            |

| DIMENSIONS / CAPACITIES |                             |  |
|-------------------------|-----------------------------|--|
| LxWxH                   | 238.8 x 116.8 x 135 cm      |  |
| Wheelbase               | 149.9 cm                    |  |
| Ground Clearance        | 27.9 cm                     |  |
| Seat Height             | 87.7 cm                     |  |
| Dry Weight*             | 372 kg                      |  |
| Rack Capacity           | Front: 45 kg<br>Rear: 90 kg |  |
| Storage Capacity        | Rear: 21.4 L                |  |
| Towing Capacity         | 590 kg                      |  |
| Fuel Capacity           | 20.5 L                      |  |

| FEATURES   |   |                   |  |
|------------|---|-------------------|--|
| Gauge      | Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock | Instrumentation   | Lighter type DC outlet in console, standard connector in the back (15-A)               |
|            |   | Lighting          | 230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light |
|            |   | Seat              | Convertible Rack System (CRS)  |
| Winch      | 1,361 kg WARN winch with roller fairlead  | Anti-theft System | RF Digitally Encoded Security System (D.E.S.S.™)                                       |
| Protection | Heavy-duty front & rear bumpers,<br>aluminum taper-profile handlebar with wind<br>deflectors and square pad   |                   |  |

| WARRANTY |                                   |
|----------|-----------------------------------|
| Factory  | 2 years                           |
| Extended | Up to 36 months B.E.S.T. coverage |



