

2026 TRAXTER XU HD11 T ABS



PACKAGE HIGHLIGHTS

- Open-4Lok front differential with ABS system
- Dynamic Power Steering (DPS)
- Brake holding mechanism
- 65 in wide with Arched Double A-Arm and sway bar
- 4,500 lb (2,041 kg) winch with synthetic cable
- Full heavy-duty HMW plastic skid plate
- Full hard roof
- LED headlights and LED tail lights with back up light
- Full heater
- Flashers
- Left and right sides EC approved mirrors
- Horn with turning signal lever
- Seat sensor
- Speed limiter: 40 - 60 Top speed (Km/h)
- ABS system

ENGINES	HD11
Type	95 hp / 70 lb-ft Rotax® ACE (Advanced Combustion Efficiency) 999 cc triple cylinder, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTCTM) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow and Electronic Drive Belt Protection L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Open-4Lok front differential with ABS system
Driving Assistance	CVT Engine Braking Sport / Normal / Work modes Speed Limiter
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched Double A-Arm with sway bar / 12 in. (30.5 cm) suspension travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	Arched Double A-Arm / 12 in. (30.5 cm) suspension travel
Rear Shocks	Twin tube gas charged shocks

TIRES / WHEELS	
Front / Rear Tires	XPS Trail King 2 27 x 9/11 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers (32 mm)
Rear	Dual 236 mm disc brakes with hydraulic single piston caliper (32 mm)
Other	Brake holding mechanism

DIMENSIONS / CAPACITIES	
Cage	Profiled cage. ROPS approved
Estimated Dry Weight*	1,890 lb (857 kg)
L x W x H	122.7 x 65 x 81 in. (312 x 165 x 206 cm)
Wheelbase	85 in. (216 cm)
Ground Clearance	14 in. (35.6 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Weather resistant above gage glove box Weather resistant passenger glove box with USB-C, USB-A & DC outlet Cubby storage and lower dash storage 3.7 gal (14 L) under seat removable bin
Towing Capacity	2,450 lb (1,111 kg)
Payload Capacity	1,500 lb (680 kg)
Fuel Capacity	11.9 gal (45 L)
Person Capacity	3

FEATURES	
Gauge	4.5 in. wide digital display with keypad
Battery	400 CCA (30 amp/h)
Magneto	650-W
Instrumentation	USB outlet Lighter DC Outlet
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights LED tail lights with flashers LED signature
Winch	4,500 lb (2,041 kg) winch with synthetic cable
Seat	Adjustable driver seat 60/40 Reinforced
Steering Wheel	Premium steering wheel with keypad space Tilt steering adjustment
Protection	Full heavy-duty HMW plastic skid plate Door safety net Lower front mudflap
Hitch Type	2 in. hitch receiver with rear hitch, tow ball and trailer connexion

WARRANTY & EXTENDED SERVICE	
Factory warranty	2-year BRP limited warranty



REQUEST A QUOTE



©2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrives GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.